

PROJECT	NOTES
CATALOG NO.	

Rev. 11/1/14

GLDL-S LED SITE LUMINAIRE

DESCRIPTION



The Daylight **S** series is a brilliant LED site and roadway luminaire that combines cutting edge optics and thermal management, with architectural flare, and function. These high performance site and roadway luminaires can meet standards no others can, while providing unmatched energy savings of up to 90%. These lights are optimal for commercial, industrial, retail, schools, and municipal facilities where aesthetics, performance, and durability are



a must. This design allows for pole and surface mount installations, and easily replaces 70-1,000W HPS or Metal Halide systems.



CHARACTERISTICS

Optical: 100 lm/Watt, 2700K–6000K, CRI 70

Electrical: 120 –277V, 347V, or 480V AC @ 700 mA or 12-30V DC, 20 to 300w models available

Mechanical: Aluminum housing, 12" W x 13-30" L by 2 ¼" high, powder coated

Certifications/Ratings: CETL/CUL, ROHS, IP66 rated, DLC Listed

Reliability: "EncapsLED" heat sink for superior cooling and durability (patent pending)

Warranty: 5 years

Options: Dimming (D); Motion Sensor (M); Twist Lock (T)

PERFORMANCE

Model #	System Wattage	5,000k Lumens
DL-S-20w	23	2,300
DL-S-30w	33	3,300
DL-S-40w	44	4,400
DL-S-50w	54	5,400
DL-S-60w	65	6,500
DL-S-70w	75	7,600
DL-S-80w	86	8,600
DL-S-90w	96	9,600
DL-S-100w	107	10,700
DL-S-110w	117	11,700
DL-S-120w	128	12,800
DL-S-130w	138	13,800
DL-S-140w	149	14,900
DL-S-150w	161	16,100



USA Made



For ordering or technical inquiries, contact:

dknagge@genesyslightgroup.com

