

PROJECT	NOTES
CATALOG NO.	

Rev. 3/15/15

GLDL-WP LED WALL PACK

DESCRIPTION

The **WP Series** wall mount LED luminaire provides excellent perimeter and security lighting. Our lightweight, low footprint aluminum fixture is easy to install and brighter than any other available. This design allows for simple surface mount installations and easily replaces 70-400W HPS or Metal Halide systems.



CHARACTERISTICS

Optical: 110-130 lm/Watt, 2700K-6000K, CRI 70 (patent pending optics)

Electrical: 120 -277V, 347V, or 480V @ 700 mA **Mechanical:**

Aluminum housing, 10" x 6" x 4" **Certifications/Ratings:** CETL/CUL, ROHS, IP66 rated, DLC Listed

Reliability: "EncapsLED" heat sink for superior cooling and durability (patent pending)

Warranty: 5 years

Options: Dimming (D); Motion Sensor (M); Twist Lock (T)



PERFORMANCE

Model #	System Wattage	Lumens @ 5000K	MH/HPS Equivalent
GLDL-WP-10W	12	1,560	70W
GLDL-WP-20w	23	2,990	70w-100W
GLDL-WP-30w	33	4,290	100W - 250W
GLDL-WP-40w	44	5,720	250W - 400W
GLDL-WP-50w	54	7,020	250W - 400W
GLDL-WP-60w	65	8,450	400W

USA Made



ORDERING INFO

Series	Wattage	Distribution	Color Temp	Luminaire Finish Color	Accessory	Voltage	Mounting
GLDL-WP	10-60W	3M-Type 3	3,000 - 6,000k	BRN - Bronze WHT - White BLK - Black SLV - Silver	00 - None PH - Photocell M- Motion Sensor DM - Dimmable	V1-120 - 277V V2-347 - 480V	EZ-5

Example: GLDL-WP-30W-3M-5000k-BRN-00-V1-EZ5

For ordering or technical inquiries, contact:

dknagge@genesyslightgroup.com,